

Material Safety Data Sheet

ECC - 22 Environmentally Preferred Contact Cleaner

Rev. 9/04/2007

2177A Flintstone Drive
Tucker, GA 30084
www.ecolink.com
email: info@ecolink.com
800/886-8240 or
770/621-8240 (9-5 EST)

FOR CHEMICAL EMERGENCY
Call INFOTRAC
800/535-5053 (24 HOURS)

Section I: Product Identification

Product name: ECC - 22
Synonym: Aliphatic Hydrocarbon
Molecular Formula: Proprietary Information

The "Plain English" Section

Material Safety Data Sheets can be confusing. Federal law requires us to print a great deal of technical information, which probably won't help the non-scientist. ECOLINK includes this "PLAIN ENGLISH" section, written to address the questions and concerns of the average person. If you have additional health, safety or product questions, don't hesitate to call us at 800/886-8240.

Health Hazards: ECC -22 is an industrial chemical. We call it "environmentally preferred" because it is intended to replace products that are more hazardous, (1,1,1 trichloroethane, HCFC-141b, MEK, etc.). This does not mean that ECC -22 is completely harmless. It is strong enough to remove industrial soils, so it can irritate your skin. We suggest you wear gloves, and avoid extended exposure to unprotected skin. Don't get it in your eyes, or breath large amounts of the vapor, (it will dry out your nasal passages). Used on a rag or from a spray bottle, the product won't produce fumes in any great quantity, (don't spray ECC - 22 under high pressure without adequate ventilation). For more exposure and first aid information, refer to MSDS Sections II, VI.

Flashpoint: ECC - 22's flashpoint is 18° F. Because of the flash point, this material is very flammable and should be handled with care. Don't use ECC - 22 or any other extremely flammable solvent around sparks, flames, and/or any source of ignition. If ECC - 22 is used on rags, the rags can ignite if exposed to an open flame because the solvent is "wicked" onto the cloth. Be sure to dispose of rags in an airtight container specifically designed to prevent combustion.

Disposal: Because ECC - 22's flashpoint is below 140°F, the liquid contents of ECC - 22 are considered a hazardous waste product, (ignitable). If you spill ECC - 22, notify the proper environmental or safety department at your company ASAP. Once ECC - 22 is contaminated with whatever you are cleaning, the resulting mixture may fall under an additional hazardous classification, depending on whether or not the material you are cleaning is hazardous. If you are not sure how to dispose of the used ECC - 22 give us a call and we will help you make the right decision.

Section II: Chemical/Hazardous Components

Chemical Name	Light Alkylation Naphtha (Petroleum)
CAS No.	64741-66-8
Approx. wt. %	90-95%
Exposure	1400 mg/m3*

* the manufacture's recommended exposure limit based upon total hydrocarbon. Otherwise not established.

Chemical Name	Carbon Dioxide
CAS No.	124-38-9
Approx. wt. %	1-5%
Exposure	ACGIH-TLV - 5000 ppm OSHA-PEL - 5000 ppm

RCRA REGULATED:	Yes (Refer to sec. VIII)
CERCLA (superfund):	Not Listed
ALL MATERIALS IN PRODUCT ARE TSCA LISTED.	
DOT Regulated:	Yes
DOT Haz. Class:	ORM-D
DOT Shipping Name:	Consumer Commodity
DOT Number:	N/A

(Questions concerning DOT information refer to DOT manual CFR 49, Chapter 1, 10/96 edition)

Section III: Physical Data

Boiling Point:	208°F (98°C)
Specific Gravity:	0.699 @ 15°C
Vapor Pressure (concentrate):	37 mm Hg @ 20°C
Melting Point:	N/A
Vapor Density (AIR=1):	3.9
Evaporation Rate (nBuAc=1):	4.3
Solubility In Water:	Negligible
Appearance & Odor:	Clear, colorless liquid with very mild petroleum odor.

Section IV: Fire and Explosion Hazard Data

Flash Point (Method):

Bulk Liquid (TCC) 18°F (-8°C)
Aerosol (USA Flame Extension) Extremely Flammable
(The "extremely flammable" designation indicates that the contents will ignite and "flash back", extending towards dispenser if sprayed on or near an ignition source.)

Autoignition Temperature: 828°F (442°C)

Flammable Limits:

LEL approx. 0.9
UEL approx. 6.3

Extinguishing Media:

Regular foam, carbon dioxide, dry chemical, class b.

Special Fire Fighting Procedures: Keep fire exposed containers cool with water. Fire fighters should wear self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate gear and chemical resistant personal protective equipment. Do not spray water directly on fire - product will float and could ignite again on surface of water.

Unusual Fire & Explosion Hazards:

Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product can ignite explosively.

Section V: Reactivity Data

Stability: Stable

Conditions to Avoid:

Sources of ignition such as sparks, hot spots, welding, flames and cigarettes.

Incompatibility (materials to avoid) : If mixed with strong oxidizers and/or acids there is the possibility of a dangerous chemical reaction.

Hazardous Decomposition:

May form carbon dioxide, various hydrocarbons, and carbon monoxide.

Hazardous Polymerization:

Will not occur.

Section VI: Health Hazard Data

Primary Routes of Exposure:

Oral, inhalation, & skin

Ingestion:

Swallowing large amounts may be harmful, by causing gastrointestinal irritation. Diarrhea, breathing difficulty, fatigue, and slight central nervous system depression may occur. Aspiration into lungs after ingestion can cause lung damage.

Inhalation:

Breathing large amounts may be harmful, by causing nose, throat, respiratory tract irritation. Difficulty

breathing, fatigue, dizziness, headaches and other central nervous system effects may follow.

Eyes:

May produce mild irritation

Skin Contact:

May cause mild irritation, redness and defatting of skin.

First Aid:

Ingestion:

Seek medical attention immediately. Manufacturer **does not** recommend inducing vomiting. If individual is drowsy or unconscious, do not give anything by mouth; place individual on left side with head down. **Note to physician** (gastric lavage using a cuffed endotracheal tube may be performed at your discretion).

Inhalation:

Remove to fresh air, if breathing is difficult give oxygen. If breathing has stopped, perform artificial respiration. Keep person warm and quiet. Seek medical attention.

Eyes:

Irrigate immediately with water for at least 15 minutes. Get medical attention if irritation persists.

Skin:

Wash with soap and water. Thoroughly clean contaminated clothes and shoes before re-use. If symptoms persist, seek medical attention.

Carcinogen:

NTP – Not Listed
IARC Monographs – None
OSHA REGS – Not Regulated

Section VII: Precautions for Safe Handling

HMIS Information:

Health – 1 / * Reactivity – 0
Flammability – 4 Personal Protection – C

HMIS Definition:

0 – Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Extreme
"/" in the Health Category denotes material does not target any major organs.
"/*" in the Health Category denotes material may target certain organs.
* target organ toxin - lung-aspiration hazard.

Eye Protection:

Safety glasses and splash protection required.

Protective Gloves: Neoprene gloves.

Respiratory Protection: Not required under conditions of normal use unless usage produces concentrations over recommended exposure limits. If vapor mist is present use NIOSH certified organic vapor mask.

Ventilation: Local exhaust/hood or fan may be used.

Other Protective Clothing: An apron may be included in the recommended personal protective gear (if splashing is likely to occur).

Work Practices: Keep material away from any sources of ignition. Only work in well ventilated areas. Store rags used with this material in an air tight, metal container to prevent spontaneous combustion. Treat this chemical with respect and follow all MSDS instructions.

Section VIII: Control Measures

Small Spill: Eliminate all sources of ignition. Make sure area is well ventilated. Absorb liquid on vermiculite, floor absorbent, or other absorbent material and transfer to hood.

Large Spill: Eliminate all ignition sources, (flares, flames including pilot lights, electrical sparks). Make sure area is well ventilated. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams, etc. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Transfer contaminated absorbent, soil and other materials to containers for disposal.

Waste Disposal Method: ECC - 22 liquid is to be disposed of according to local, state, and federal regulations. The manufacture recommends incineration when disposing of waste material. Please call us if you need additional disposal information.

Under RCRA this material is considered a hazardous waste due to the flash point. The EPA hazardous waste number is D001.

Precautions To Be Taken In Handling & Storing: CONTENTS UNDER PRESSURE. Do not store at temperatures exceeding 120°F or in direct sunlight. Do not puncture or incinerate container. Any use of this product should be thoroughly evaluated to establish and maintain safe operating conditions.

Other Precautions: Keep this and all chemicals out of the reach of children.

Section IX: Part Number and Packaging

Product Name Part No. Packaging

ECC - 22 654-1 12 x 15.85 oz net Aerosol

DISCLAIMER: Ecolink, Inc. believes the information contained herein is accurate. However, Ecolink makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained by the use thereof. Ecolink, Inc. assumes no responsibility for injury from the use of the product described herein.

END OF MSDS